

LIGHTOLIER®

Performance Recessed CFL Downlighting **1001FR**

Page 1 of 1

5" Aperture, 1 Light, Compact Fluorescent, Non-IC, Remodeler, Frame-In Kit





Complete Fixture consists of Frame-In Kit and Reflector Trim. Select each separately.

Uniframe [™] C	ompact Flu	orescent P	erformance	Series Refle	ctor Trims		
Vertical Open	Vertical Wall Wash - Single	Vertical Wall Wash - Double	Horizontal Open	Horizontal Wall Wash - Single			Horizontal Cross Blade
1001CL 1001CD 1001WH	1001CLSW 1001CDSW 1001WHSW	1001CLDW 1001CDDW 1001WHDW	1001HCL 1001HCD 1001HWH	1001HCLSW 1001HCDSW 1001HWHSW	Clear Lens 1001HCLC 1001HCDC 1001HWHC Opal Lens 1001HCLO 1001HCDO 1001HWHO	Fresnel 1001HCLF 1001HCDF 1001HWHF	1001HACB 1001HWHCB
Universal Series Reflector Trims (Reference Trim Spec Sheet for Recommended Lamping)							ng)
Performance Cone	Cone	Satin Cone	Baffle	Wall Wash	Wet Location		
1013CFL 1013CDCFL	1012* 1013* 1013BK* 1013WH 1013CD* 1071 1045 1046 1046CD	1008* 1010*	1005* 1005BNM 1005WH 1076 1076WH	1035 1035WH 1085 1095 1096 1096CD	1021** 1024 1078		
	Vertical Open 1001CL 1001CD 1001WH Universal Se Performance Cone 1013CFL	Vertical Open Vertical Wall Wash - Single 1001CL 1001CD 1001WH 1001CLSW 1001WHSW Universal Series Reflect Performance Cone 1013CFL 1013CFL 1012* 1013K* 1013BK* 1013WH 1013CD* 1071 1045 1046	Vertical Open Vertical Wall Wash - Single Vertical Wall Wash - Double 1001CL 1001CD 1001WH 1001CLSW 1001WHSW 1001CLDW 1001CDW 1001WHSW Universal Series Reflector Trims (F Performance Cone Satin Cone 1013CFL 1013CFL 1012* 1013K* 1013K* 1013WH 1013CD* 1071 1045 1046 100*	Vertical Open Vertical Wall Wash - Single Vertical Wall Wash - Double Horizontal Open 1001CL 1001CD 1001CD 1001WH 1001CLSW 1001CDSW 1001WHSW 1001CLDW 1001WHDW 1001HCL 1001HCD 1001WHDW Universal Series Reflector Trims (Reference Tri Performance Cone Satin Cone Baffle 1013CFL 1013CFL 1012* 1013K* 1013BK* 1013CD* 1076 1005* 1076WH 1005WH 1076 1076WH 1076 1076WH 1076WH 1076WH	Vertical Open Vertical Wall Wash - Single Vertical Wall Wash - Double Horizontal Open Horizontal Wash - Single 1001CL 1001CD 1001CD 1001WH 1001CLSW 1001CDW 1001WHSW 1001CLDW 1001CDW 1001WHDW 1001HCL 1001HCD 1001HWH 1001HCLSW 1001HWH Universal Series Reflector Trims (Reference Trim Spec Sheet f Performance Cone Satin Cone Baffle Wall Wash 1013CFL 1013CFL 1012* 1013K* 1013WH 1008* 1010* 1005* 1005BNM 1035 1035WH 1035WH 1035WH 1095 1035 1095 1013CD* 1013CD* 1046 1045 1046 1096 1096	Wash - Single Wash - Double Open Wash - Single Lensed 1001CL 1001CD 1001CD 1001WH 1001CLSW 1001WHSW 1001CDW 1001WHDW 1001HCL 1001WHDW 1001HCL 1001HWH 1001HCLSW 1001HWHSW 1001HCLC 1001HWHSW 1001HCLC 1001HWHSW Vniversal Series Reflector Trims (Reference Trim Spec Sheet for Recomme Performance Cone Satin Cone Baffle Wall Wash Wet Location 1013CFL 1013CDCFL 1012* 1013K* 1013WH 1013CD* 10171 1045 1046 1008* 1076 1005* 1076WH 1035 1096CD 1078	Vertical OpenVertical Wall Wash - SingleVertical Wall Wash - DoubleHorizontal OpenHorizontal Wall Wash - SingleHorizontal Wet Location Lensed / Diffused1001CL 1001CD 1001CD 1001WH1001CLDW 1001WHSW1001CDW 1001WHDW1001HCL 1001HCD 1001HWH1001HCLSW 1001HCD 1001HWHSW1001HCLF 1001HCLF 1001HWHSWClear Lens 1001HCLC 1001HCLF 1001HCLF 1001HWHSWFresnel 1001HCLF 1001HWHSWUniversal Series Reflector Trims (Reference Trim Spec Sheet for Recommended Lampin 1013CFL 1013CFLNet Location 1012** 1013* 1013**Net Location 1005** 1005** 1005** 1005WH 1005WH 1005WH 1005WH 1005SHNM 1035WH 1035WH 1035WH 1035WH 1021** 1021** 1036CDWall Wash 1021** 1021** 1024 1078

*Add NM suffix to catalog number for Natural Metal flange and finish.

**Only compatible with 18W Quad lamp.

Features

- UniFrame™ Mounting Ring: .032" (#22ga.) thick Galvanized Steel. Accommodates existing ceilings up to 2" thick. Attaches securely to any type of ceiling material without tools using (3) mounting straps provided. Includes adhesive backed aperture template.
- 2. Trim Clips: "Push In / Twist Out" clips hold reflector flush to ceiling.
- **3. Junction Box:** 2" x 4" x 3-1/2" (22cu.in.) .032" (#22ga.) galvanized steel. UL Listed for 90° C supply wire. Attaches to mounting ring without tools.
- Ballast: 120V 277V UL Listed Electronic Ballast, end of lamp life protection, class "P" thermally protected, class "A" sound rating.
- Socket: Four-pin base, molded thermoplastic socket, prewired with No. 18 AWM leads to ballast.
- 6. Socket Housing: .036" (#20ga.) Galvanized Steel housing attaches to reflector trim by spring clip for precise optic alignment.

Labels

cULus Listed. Suitable for Damp Locations.

Job Information	Туре:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710 We reserve the right to change details of design, materials and finish. www.lightolier.com © 2008 Philips Group • F0708

Lightolier is a Philips group brand

PHILIPS